

Acrobat 2X

Touchless rollover car wash

High-pressure washing with no brush contact, for vehicles whose finish or livery must not be touched. Two arms move in six axes on a supporting bridge under PLC control.



2.20m

Washing height

3-5 veh/min

Operation time

Specification

Measurement	Unit	ACROBAT 2X
Maximum machine width	m	4.20
Maximum machine height	m	3.20
Maximum washing height	m	2.20
Maximum washing width	m	2.20
Plant length	m	6.5 – 15
Operation time	vehicle/min	3 – 5
Water pump pressure	bar	100 / 200
Feedwater pressure	bar	3.5 / 4
Water consumption	lt/vehicle	18 – 250

Measurement	Unit	ACROBAT 2X
Air pressure	bar	6
Air requirement	lt/min	20
Operating voltage	V	400
Installed power, washing only	kW	35
Installed power, drying only	kW	33
Installed power, all units	kW	75
Electricity	kW/vehicle	0.75 / 2.50
Chemical foam	gr/vehicle	20 – 30
Wax	gr/vehicle	20

Supplied with the machine: door to door shipping, installation, and six months warranty. Send us the site and the vehicles you expect to wash and we will return a proforma quotation at no charge.

Email
sales@europemakine.com

Telephone
+1 561 825 7363